




HYDRAULIC GEAR
PUMPS AND
MOTORS

FEATURES

Modular design and versatility are the main features of “MAGNUM” series gear pumps and motors. Mounting flange, body and rear cover can be easily assembled to obtain multiple pumps of same or different groups available in standard version, common inlet or separated stages. Wide selection of drive shafts and mounting flanges in SAE version with the possibility of integrated outboard bearing to suit all the applications with axial and radial load on the drive shaft.

Port locations available in side or rear locations, and combination of side and rear locations. The low level of noise emission with the high volumetric and overall efficiencies ensure reliability and long working life in heavy duty applications.

DISPLACEMENTS

From 1.05 in³/rev (17,28 cm³/rev)
To 7.66 in³/rev (125,63 cm³/rev)


PRESSURE

Max. continuous 4060 psi (280 bar)
Max. intermittent 4350 psi (300 bar)
Max. peak 4640 psi (320 bar)

MAX. SPEED

3000 min⁻¹

- Wide range of drive shafts and mounting flanges in SAE version
- More choices of port locations
- Integrated outboard bearing for heavy duty applications
- Multiple units available in standard version, common inlet and separated stages
- Exceptional working life expectancy



1	Mounting flange
2	Thrust plate
3	Body
4	Rear cover
5	Gear
6	Seal
7	Shaft seal

01/07.2005

FEATURES

Construction	External gear type pumps and motors
Mounting	SAE flanges
Line connections	Screw and flange
Direction of rotation (looking at the drive shaft)	Anti-clock (S) - clockwise (D) - reversible external drain (R) reversible internal drain (B)
Inlet pressure range for pumps	10 ÷ 44 psi - [0,7 ÷ 3 bar (abs.)]
Max back pressure for single rotation motors	p ₁ (continuous) max 73 psi (5 bar)
	p ₂ (for 20 s) max 116 psi (8 bar)
	p ₃ (for 8 s) max 218 psi (15 bar)
Max drain line pressure on reversible rotation motors	73 psi (5 bar)
Max back pressure on the series motors	2175 psi (150 bar)
Fluid temperature range	See table (1)
Fluid	Mineral oil based hydraulic fluids to ISO/DIN and fire resistant fluids [see table (1)]. For other fluids please consult our technical sales department.
Viscosity range	From 60 to 456 SSU [12 to 100 mm ² /s (cSt)] recommended
	Up to 3410 SSU [750 mm ² /s (cSt)] permitted
Filtering requirement	See table (2)

Replaces: 01/07.2005

Tab. 1

Type	Fluid composition	Max pressure psi - (bar)	Max speed min ⁻¹	Temperature °F - (°C)			Seals (◆)
				Min	Max continuous	Max peak	
ISO/DIN	Mineral oil based hydraulic fluid to ISO/DIN	See page 6	See page 6	-13 (-25)	176 (80)	212 (100)	N
				-13 (-25)	230 (110)	257 (125)	N - H
HFA	Oil emulsion in water 5 ÷ 15% of oil	725 (50)	1500	36 (2)	131 (55)		N
HFB	Water emulsion in oil 40% of water	1740 (120)	1500	36 (2)	140 (60)		N
HFC	Water - glycol	1450 (100)	1500	-4 (-20)	140 (60)		N Bz
HFD	Phosphate ester	2175 (150)	1500	14 (-10)	176 (80)		V Bz

(◆) **N**= Buna N (standard) - **N-H**= Buna N and high back pressure shaft seals - **V**= Viton
N Bz= Buna N and Bronze thrust plates - **V Bz**= Viton and Bronze thrust plates

Tab. 2

Working pressure psi (bar)	$\Delta p < 2030$ $\Delta p < (140)$	$2030 < \Delta p < 3045$ $(140) < \Delta p < (210)$	$\Delta p > 3045$ $\Delta p > (210)$
Contamination class NAS 1638	10	9	8
Contamination class ISO 4406:1999	21/19/16	20/18/15	19/17/14
Achieved with filter $\beta_{10(c)} \geq 200$ according to ISO 16889	-	10 μ m	10 μ m
Achieved with filter $\beta_{25(c)} \geq 200$ according to ISO 16889	25 μ m	-	-

Casappa recommends to use
its own production filters:



02/06.2012

GENERAL NOTES


Available with different inlet and outlet ports.

If you use fire resistant fluids, specify the fluid type when ordering.


For more information please consult our technical sales department.

FEATURES


DEFINITION OF ROTATION DIRECTION LOOKING AT THE DRIVE SHAFT




Anti-clock rotation




Clockwise rotation



Reversible rotation



PRESSURE DEFINITION



p_1 Max. continuous pressure
 p_2 Max. intermittent pressure
 p_3 Max. peak pressure

GENERAL DATA PUMPS AND MOTORS

Pump type HDP Motor type HDM	Displacement	Max. pressure			Max. speed	Min. speed
		p ₁	p ₂	p ₃		
	in ³ /rev (cm ³ /rev)	psi (bar)			min ⁻¹	
HD. 30•17	1.05 (17,28)	4060 (280)	4350 (300)	4640 (320)	3000	400
HD. 30•22	1.34 (21,99)	4060 (280)	4350 (300)	4640 (320)	3000	400
HD. 30•24	1.47 (24,03)	4060 (280)	4350 (300)	4640 (320)	3000	400
HD. 30•27	1.63 (26,70)	4060 (280)	4350 (300)	4640 (320)	3000	400
HD. 30•34	2.11 (34,56)	3915 (270)	4205 (290)	4495 (310)	3000	400
HD. 30•38	2.40 (39,27)	3915 (270)	4205 (290)	4495 (310)	3000	400
HD. 30•43	2.68 (43,98)	3770 (260)	4060 (280)	4350 (300)	3000	400
HD. 30•51	3.16 (51,83)	3335 (230)	3770 (260)	4060 (280)	2500	300
HD. 30•56	3.45 (56,55)	3118 (215)	3553 (245)	3843 (265)	2500	300
HD. 30•61	3.74 (61,26)	2900 (200)	3335 (230)	3625 (250)	2000	250
HD. 30•73	4.50 (73,82)	2755 (190)	3045 (210)	3335 (230)	1700	250
HD. 30•82	4.98 (81,68)	2465 (170)	2755 (190)	3045 (210)	1500	250
HD. 35•40	2.47 (40,46)	3915 (270)	4060 (280)	4495 (310)	3000	400
HD. 35•50	3.12 (51,10)	3915 (270)	4060 (280)	4495 (310)	3000	400
HD. 35•63	3.90 (63,88)	3915 (270)	4060 (280)	4495 (310)	3000	400
HD. 35•71	4.42 (72,40)	3625 (250)	4060 (280)	4350 (300)	3000	400
HD. 35•80	4.94 (80,91)	3625 (250)	4060 (280)	4350 (300)	3000	400
HD. 35•90	5.59 (91,56)	3335 (230)	3770 (260)	4060 (280)	2700	400
HD. 35•100	6.10 (100,08)	3045 (210)	3480 (240)	3770 (260)	2700	400
HD. 35•112	6.88 (112,85)	2755 (190)	3190 (220)	3480 (240)	2700	400
HD. 35•125	7.66 (125,63)	2465 (170)	2900 (200)	3190 (220)	2500	250

p₁ = Max. continuous pressure

p₂ = Max. intermittent pressure

p₃ = Max. peak pressure

The values in the table refer to unidirectional pumps and motors.

Reversible pump and motors max pressures are 15% lower than those shown in table.

For different working conditions please consult our sales department.

01/07.2005

GENERAL DATA PUMPS AND MOTORS

Replaces: 01/07.2005

Q	US gpm (l/min)	Flow
M	lbf in (Nm)	Torque
P	HP (kW)	Power
V	in ³ /rev (cm ³ /rev)	Displacement
n	min ⁻¹	Speed
Δp	psi (bar)	Pressure

Efficiencies

		Pumps	Motor
$\eta_v = \eta_v(V, \Delta p, n)$	Volumetric efficiency	($\approx 0,98$)	($\approx 0,97$)
$\eta_{hm} = \eta_{hm}(V, \Delta p, n)$	Hydro-mechanical efficiency	($\approx 0,90$)	($\approx 0,88$)
$\eta_t = \eta_v \cdot \eta_{hm}$	Overall efficiency	($\approx 0,88$)	($\approx 0,85$)

Design calculations for pump ○

$$Q = Q_{theor.} \cdot \eta_v$$

$$Q_{theor.} = \frac{V \text{ (cm}^3\text{/rev)} \cdot n \text{ (min}^{-1}\text{)}}{1000} \quad [\text{l/min}]$$

$$M = \frac{M_{theor.}}{\eta_{hm}} \quad [\text{Nm}]$$

$$M_{theor.} = \frac{\Delta p \text{ (bar)} \cdot V \text{ (cm}^3\text{/rev)}}{62,83}$$

$$P_{IN} = \frac{P_{OUT}}{\eta_t} \quad [\text{kW}]$$

$$P_{OUT} = \frac{\Delta p \text{ (bar)} \cdot Q \text{ (l/min)}}{600}$$

Design calculations for motor ○

$$Q = \frac{Q_{theor.}}{\eta_v} \quad [\text{l/min}]$$

$$Q_{theor.} = \frac{V \text{ (cm}^3\text{/rev)} \cdot n \text{ (min}^{-1}\text{)}}{1000}$$

$$M = M_{theor.} \cdot \eta_{hm} \quad [\text{Nm}]$$

$$M_{theor.} = \frac{\Delta p \text{ (bar)} \cdot V \text{ (cm}^3\text{/rev)}}{62,83}$$

$$P_{IN} = \frac{\Delta p \text{ (bar)} \cdot Q \text{ (l/min)}}{600} \quad [\text{kW}]$$

$$P_{OUT} = P_{IN} \cdot \eta_t$$


○ 02/06.2012

Note: Diagrams providing approximate selection data will be found on subsequent pages.

HDM 30

MAGNUM 30 GEAR MOTORS PERFORMANCE CURVES


Replaces: 01/07.2005



Each curve has been obtained at 122 °F (50°C), using oil with viscosity 168 SSU (36 cSt) at 104 °F (40°C) and at these pressures:

HDP 30•17	—	290 psi (20 bar)
	- -	4060 psi (280 bar)
HDP 30•22	—	290 psi (20 bar)
	- -	4060 psi (280 bar)
HDP 30•27	—	290 psi (20 bar)
	- -	4060 psi (280 bar)
HDP 30•34	—	290 psi (20 bar)
	- -	3915 psi (270 bar)
HDP 30•43	—	290 psi (20 bar)
	- -	3770 psi (260 bar)
HDP 30•51	—	290 psi (20 bar)
	- -	3335 psi (230 bar)
HDP 30•61	—	290 psi (20 bar)
	- -	2900 psi (200 bar)
HDP 30•73	—	290 psi (20 bar)
	- -	2755 psi (190 bar)
HDP 30•82	—	290 psi (20 bar)
	- -	2465 psi (170 bar)

O 02/06.2012




New displacements

HDP 30•24	—	290 psi (20 bar)
	- -	4060 psi (280 bar)
HDP 30•38	—	290 psi (20 bar)
	- -	3915 psi (270 bar)
HDP 30•56	—	290 psi (20 bar)
	- -	3118 psi (215 bar)


HDM 30

MAGNUM 30 GEAR MOTORS PERFORMANCE CURVES


HDM 30•17




HDM 30•22



HDM 30•24



HDM 30•27




01/07.2005


HDM 30

MAGNUM 30 GEAR MOTORS PERFORMANCE CURVES


HDM 30•34




HDM 30•38



HDM 30•43



HDM 30•51




01/07.2005


HDM 30

MAGNUM 30 GEAR MOTORS PERFORMANCE CURVES


HDM 30•56




HDM 30•61



HDM 30•73



HDM 30•82





01/07.2005

SINGLE UNITS SIDE PORTS

L

D010-D01/0405



Tightening torque
Nm (lbf in)

V

280 ^{±28} (2230 ÷ 2726)

DRIVE SHAFTS:
see page 47

MOUNTING FLANGE:
see page 48 ÷ 50

PORTS:
see page 51


The drawing shows a single unit with left rotation.

Pump type Motor type	A	B	C	D	E (IN)	F (OUT)
	mm (inch)	mm (inch)	mm (inch)	mm (inch)	mm (inch)	mm (inch)
HD. 30•17	184,5 (7.2638)	138 (5.4331)				
HD. 30•22	187,5 (7.3819)	141 (5.5512)				
HD. 30•24	188,8 (7.4331)	142,3 (5.6024)				
HD. 30•27	190,5 (7.5000)	144 (5.6693)				
HD. 30•34	195,5 (7.6969)	149 (5.8661)				
HD. 30•38	198,5 (7.8150)	152 (5.9843)	23,45	150	80	75
HD. 30•43	201,5 (7.9331)	155 (6.1024)	(0.9232)	(5.9055)	(3.1496)	(2.9528)
HD. 30•51	206,5 (8.1299)	160 (6.2992)				
HD. 30•56	209,5 (8.2480)	163 (6.4173)				
HD. 30•61	212,5 (8.3661)	166 (6.5354)				
HD. 30•73	220,5 (8.6811)	174 (6.8504)				
HD. 30•82	225,5 (8.8780)	179 (7.0472)				
HD. 35•40	224,5 (8.8386)	172 (6.7717)				
HD. 35•50	229,5 (9.0354)	177 (6.9685)				
HD. 35•63	235,5 (9.2717)	183 (7.2047)				
HD. 35•71	239,5 (9.4291)	187 (7.3622)				
HD. 35•80	243,5 (9.5866)	191 (7.5197)	27,35	172	90	85
HD. 35•90	248,5 (9.7835)	196 (7.7165)	(1.0768)	(6.7717)	(3.5433)	(3.3465)
HD. 35•100	252,5 (9.9409)	200 (7.8740)				
HD. 35•112	258,5 (10.1772)	206 (8.1102)				
HD. 35•125	264,5 (10.4134)	212 (8.3465)				

01/07.2005

SINGLE UNITS REAR PORTS

P



Tightening torque
Nm (lbf in)

V

280 ± 28 (2230 $\div$ 2726)

DRIVE SHAFTS:
see page 47

MOUNTING FLANGE:
see page 48 $\div$ 50

PORTS:
see page 51

The drawing shows a single unit with left rotation.


01/07.2005

Pump type Motor type	A	B	C	D	E	F	G
	mm (inch)	mm (inch)	mm (inch)	mm (inch)	mm (inch)	mm (inch)	mm (inch)
HD. 30•17	184,5 (7.2638)	173 (6.8110)					
HD. 30•22	187,5 (7.3819)	176 (6.9291)					
HD. 30•24	188,8 (7.4331)	177,3 (6.9803)					
HD. 30•27	190,5 (7.5000)	179 (7.0472)					
HD. 30•34	195,5 (7.6969)	184 (7.2441)					
HD. 30•38	198,5 (7.8150)	187 (7.3622)	23,45	150	80	75	75
HD. 30•43	201,5 (7.9331)	190 (7.4803)	(0.9232)	(5.9055)	(3.1496)	(2.9528)	(2.9528)
HD. 30•51	206,5 (8.1299)	195 (7.6772)					
HD. 30•56	209,5 (8.2480)	198 (7.7953)					
HD. 30•61	212,5 (8.3661)	201 (7.9134)					
HD. 30•73	220,5 (8.6811)	209 (8.2283)					
HD. 30•82	225,5 (8.8780)	214 (8.4252)					
HD. 35•40	224,5 (8.8386)	213 (8.3858)					
HD. 35•50	229,5 (9.0354)	218 (8.5827)					
HD. 35•63	235,5 (9.2717)	224 (8.8189)					
HD. 35•71	239,5 (9.4291)	228 (8.9764)					
HD. 35•80	243,5 (9.5866)	232 (9.1339)	27,35	172	90	85	89
HD. 35•90	248,5 (9.7835)	237 (9.3307)	(1.0768)	(6.7717)	(3.5433)	(3.3465)	(3.5039)
HD. 35•100	252,5 (9.9409)	241 (9.4882)					
HD. 35•112	258,5 (10.1772)	247 (9.7244)					
HD. 35•125	264,5 (10.4134)	253 (9.9606)					

VERSIONS

For each version, the possible combination between drive shafts and mounting flanges are shown on pages 48 ÷ 50.


0



D0 10-D 11/0594

Version for applications without radial and axial load on the drive shaft.


1



D0 10-D 12/0594

Version for applications with low radial load and without axial load on the drive shaft.

2




D0 10-D 13/0594

Special version with independent shaft for applications with low radial load and without axial load on the drive shaft.

Max. torque version 2:
HD. 30: 170 Nm (1505 lbf in)
HD. 35: 350 Nm (3098 lbf in)

3




D0 10-138/0505

Version for applications with radial and axial load on the drive shaft.

Max. torque version 3:
HD. 30: 170 Nm (1505 lbf in)
HD. 35: 350 Nm (3098 lbf in)

4




D0 10-D 14/0594

Version for applications with radial and axial load on the drive shaft.

Max. torque version 4:
HD. 30: 170 Nm (1505 lbf in)

4



D0 10-139/0505

Version for applications with radial and axial load on the drive shaft.

Max. torque version 4:
HD. 35: 350 Nm (3098 lbf in)


01/07.2005

For the outboard bearings life expectancy, diagrams providing approximate selection data will be found on subsequent pages.
For particular applications please consult our technical sales department.

VERSION WITH OUTBOARD BEARING MAGNUM 30

3

D010-143/0405



X = Distance of the radial load result from the mounting flange [mm(in)].

Each curve has been obtained at:


Lubricant oil ISO VG 46

Temperature 140 °F (60 °C)

Without or with very low axial load

Example

Fr Radial load	1000 N (225.0 lbf)
X	30 mm (1.1811 in)
Speed	2000 min ⁻¹
Rating fatigue life	≈ 1915 h



01/07.2005

D010-147/0605


DRIVE SHAFTS

SAE "B" SPLINE

04

Mounting face refer to flange code **S3**

Ext. Involute Spline SAE J498B
with major diameter modified
13 teeth - 16/32 Pitch - 30 deg
Flat Root - Side fit - Class 1



HD. 30 MAX 330 Nm (2921 lbf in) ◆


HD. 35 MAX 300 Nm (2655 lbf in) ◆

SAE "BB" SPLINE

05

Mounting face refer to flange code **S3**

Ext. Involute Spline SAE J498B
with major diameter modified
15 teeth - 16/32 Spline - 30 deg
Flat Root - Side fit - Class 1




HD. 30 MAX 500 Nm (4426 lbf in) ◆

HD. 35 MAX 450 Nm (3983 lbf in) ◆

SAE "C" SPLINE

06

Mounting face refer to flange code **S8**




HD. 30 MAX 170 Nm (1505 lbf in) ◆

HD. 35 MAX 900 Nm (7966 lbf in) ◆

SAE "B" STRAIGHT

32

Mounting face refer to flange code **S3**




MAX 200 Nm (1770 lbf in) ◆

SAE "BB" STRAIGHT

33

Mounting face refer to flange code **S3**




MAX 280 Nm (2478 lbf in) ◆

SAE "C" STRAIGHT

34

Mounting face refer to flange code **S8**



MAX 600 Nm (5311 lbf in) ◆


◆ For "2", "3" and "4" version whichever end shaft, the max torque applicable is:
HD. 30 MAX 170 Nm (1505 lbf in) - HD. 35 MAX 350 Nm (3098 lbf in)

MOUNTING FLANGES AND TABLE OF COMPATIBILITY

SAE "A" 2 HOLES

S1

Conforms to SAE J744



DRIVE SHAFTS

See page 47


GROUP	VERSIONS See page 42	04	32	05	33	06	34
HD. 30	0	X	X	X	X		
	1	X	X	X	X		
	2	X	X	X	X	X	X

X Available combination

SAE "B" 2-4 HOLES

S3

Conforms to SAE J744



DRIVE SHAFTS

See page 47

GROUP	VERSIONS See page 42	04	32	05	33	06	34
HD. 30	0	X	X	X	X		
	1	X	X	X	X		
	2	X	X	X	X	X	X
	3	X	X	X		X	X
	4	X	X		X	X	X

X Available combination


01/07.2005

MOUNTING FLANGES AND TABLE OF COMPATIBILITY

SAE "C" 2-4 HOLES

S8

Conforms to SAE J744



D010-D10/0505

GROUP	A	B
	mm (inch)	mm (inch)
HD. 30	80 (3.1496)	167,9 (6.6102)
HD. 35	90 (3.5433)	182,8 (7.1969)

DRIVE SHAFTS See page 47

O

GROUP	VERSIONS See page 42	04	32	05	33	06	34
HD. 30	0	X	X	X	X		
	1	X	X	X			
	2	X	X	X	X	X	X
	3	X	X	X		X	X
	4	X	X		X	X	X
HD. 35	0					X	X
	1					X	X
	2	X	X	X	X	X	X
	3					X	X
	4	X				X	X

X Available combination

Replaces: 01/07.2005


O 02/06.2012

MOUNTING FLANGES AND TABLE OF COMPATIBILITY

SAE "B" 4 HOLES

S4

Conforms to SAE J744



DRIVE SHAFTS

See page 47


GROUP	VERSIONS See page 42	04	32	05	33	06	34
HD. 35	0					X	X
	1					X	X
	2	X	X			X	X
	3					X	X
	4	X				X	X

X Available combination

SAE "B" 2 HOLES

S5

Conforms to SAE J744



DRIVE SHAFTS


See page 47

GROUP	VERSIONS See page 42	04	32	05	33	06	34
HD. 35	0					X	X
	1					X	X
	2	X	X	X	X	X	X
	3					X	X
	4	X				X	X

X Available combination

01/07.2005

PORTS TYPE



PORTS TYPE	SIDE PORTS								REAR PORTS			
	Split SSM		Spit SSS		Gas BSPP		SAE ODT		Gas BSPP		SAE ODT	
Pump type	IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT
Motor type	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN
HD. 30•17	MC	MB	SC	SB	GF	GE	OF	OD	GE	GE	OD	OD
HD. 30•22	MC	MB	SC	SB	GF	GE	OF	OD	GE	GE	OD	OD
HD. 30•27	MC	MB	SC	SB	GF	GE	OF	OD	GE	GE	OD	OD
HD. 30•34	MC	MB	SC	SB	GF	GE	OF	OD	GE	GE	OD	OD
HD. 30•38	MC	MB	SC	SB	GF	GE	OF	OD	GE	GE		
HD. 30•43	MD	MC	SD	SC	GG	GF	OG	OF	GF (●)	GE		
HD. 30•51	MD	MC	SD	SC	GG	GF	OG	OF	GF (●)	GE		
HD. 30•56	MD	MC	SD	SC	GG	GF	OG	OF	GF (●)	GE		
HD. 30•61	ME	MD	SE	SD	GG	GF	OG	OF	GF (●)	GE		
HD. 30•73	ME	MD	SE	SD	GG	GF	OG	OF	GF (●)	GE		
HD. 30•82	ME	MD	SE	SD	GG	GF	OG	OF	GF (●)	GE		
HD. 35•40	ME	MD	SE	SD	GH	GG	OG	OF	GG (●)	GF	OF OH (◆)	OD OG (◆)
HD. 35•50	ME	MD	SE	SD	GH	GG	OG	OF	GG (●)	GF	OF OH (◆)	OD OG (◆)
HD. 35•63	ME	MD	SE	SD	GH	GG	OG	OF	GG (●)	GF	OF OH (◆)	OD OG (◆)
HD. 35•71	ME	MD	SE	SD	GH	GG	OG	OF	GG (●)	GF	OF OH (◆)	OD OG (◆)
HD. 35•80	ME	MD	SE	SD	GH	GG	OG	OF	GG (●)	GF	OF OH (◆)	OD OG (◆)
HD. 35•90	MF	ME	SF	SE	GL	GH	OH	OG	GG (●)	GF		
HD. 35•100	MF	ME	SF	SE	GL	GH	OH	OG	GG (●)	GF		
HD. 35•112	MF	ME	SF	SE	GL	GH	OH	OG				
HD. 35•125	MF	ME	SF	SE	GL	GH	OH	OG				

(●) Not available for reversible pumps and motors with external drain.

(◆) Available only for single pumps with larger ports.

01/07.2005

PORTS SIZE



Tightening torque for low pressure side port



Tightening torque for high pressure side port [values obtained at 5075 psi (350 bar)]

For reversible rotation, please consult only the tightening torque for high pressure side port


SAE FLANGED PORTS J518 - Standard pressure series 3000 PSI

SSM

Metric thread ISO 60° conforms to ISO/R 262

CODE	A	B	C	D		
	mm (in)	mm (in)	mm (in)	Thread Depth mm (in)	Nm (lbf in)	Nm (lbf in)
MB	19 (0.7480)	47,6 (1.8740)	22,2 (0.8740)	M 10 22 (0.8661)	20 ⁺¹ (177 ÷ 186)	35 ^{+2,5} (310 ÷ 332)
MC	24,5 (0.9646)	52,4 (2.0630)	26,2 (1.0315)	M 10 22 (0.8661)	20 ⁺¹ (177 ÷ 186)	35 ^{+2,5} (310 ÷ 332)
MD	30,5 (1.2008)	58,7 (2.3110)	30,2 (1.1890)	M 10 22 (0.8661)	20 ⁺¹ (177 ÷ 186)	35 ^{+2,5} (310 ÷ 332)
ME	39,3 (1.5472)	69,8 (2.7480)	35,7 (1.4055)	M 12 27 (1.0630)	30 ^{+2,5} (266 ÷ 288)	65 ⁺⁵ (575 ÷ 620)
MF	51 (2.0079)	77,8 (3.0630)	42,9 (1.6890)	M 12 27 (1.0630)	30 ^{+2,5} (266 ÷ 288)	—

D010-D15/0405




SAE FLANGED PORTS J518 - Standard pressure series 3000 PSI

SSS

American straight thread UNC-UNF 60° conforms to ANSI B 1.1

CODE	A	B	C	D		
	mm (in)	mm (in)	mm (in)	Thread Depth mm (in)	Nm (lbf in)	Nm (lbf in)
SB	19 (0.7480)	47,6 (1.8740)	22,2 (0.8740)	3/8 - 16 UNC-2B 22 (0.8661)	20 ⁺¹ (177 ÷ 186)	30 ^{+2,5} (266 ÷ 288)
SC	24,5 (0.9646)	52,4 (2.0630)	26,2 (1.0315)	3/8 - 16 UNC-2B 22 (0.8661)	20 ⁺¹ (177 ÷ 186)	30 ^{+2,5} (266 ÷ 288)
SD	30,5 (1.2008)	58,7 (2.3110)	30,2 (1.1890)	7/16 - 14 UNC-2B 28,5 (1.1220)	25 ⁺¹ (221 ÷ 230)	55 ⁺⁵ (487 ÷ 531)
				7/16 - 14 UNC-2B 27 (1.0630) (◆)		
SE	39,3 (1.5472)	69,8 (2.7480)	35,7 (1.4055)	1/2 - 13 UNC-2B 27 (1.0630)	30 ^{+2,5} (266 ÷ 288)	70 ⁺⁵ (620 ÷ 664)
SF	51 (2.0079)	77,8 (3.0630)	42,9 (1.6890)	1/2 - 13 UNC-2B 27 (1.0630)	30 ^{+2,5} (266 ÷ 288)	—

D010-D15/0405



(◆) For MAGNUM 35

PORTS SIZE



Tightening torque for low pressure side port




Tightening torque for high pressure side port [values obtained at 5075 psi (350 bar)]

For reversible rotation, please consult only the tightening torque for high pressure side port

GAS STRAIGHT THREAD PORTS

BSPP

British standard pipe parallel (55°) conforms to UNI - ISO 228



CODE	Nominal size	A	Ø B	Ø C	D	E		
			mm (in)	mm (in)	mm (in)	mm (in)	Nm (lbf in)	Nm (lbf in)
GC (◆)	3/8"	G 3/8	25 (0.9843)	15 (0.5906)	14 (0.5512)	4 (0.1575)	15 ⁺¹ (133 ÷ 142)	—
GE	3/4"	G 3/4	—	24,5 (0.9646)	22 (0.8661)	—	30 ^{+2,5} (266 ÷ 288)	90 ⁺⁵ (797 ÷ 841)
GF	1"	G 1	—	30,5 (1.2008)	25 (0.9843)	—	50 ^{+2,5} (443 ÷ 465)	130 ⁺¹⁰ (1151 ÷ 1239)
GG	1" 1/4	G 1 1/4	—	39 (1.5354)	26 (1.0236)	—	60 ⁺⁵ (531 ÷ 575)	170 ⁺¹⁰ (1505 ÷ 1593)
GH	1" 1/2	G 1 1/2	—	45 (1.7716)	28 (1.1024)	—	70 ⁺⁵ (620 ÷ 664)	210 ⁺¹⁰ (1859 ÷ 1947)
GL	2"	G 2	—	57 (2.2441)	32 (1.2598)	—	150 ⁺¹⁰ (1328 ÷ 1416)	—

(◆) = Drain port

01/07.2005

PORTS SIZE



Tightening torque for low pressure side port



Tightening torque for high pressure side port [values obtained at 5075 psi (350 bar)]


For reversible rotation, please consult only the tightening torque for high pressure side port

SAE STRAIGHT THREAD PORTS J514

ODT

American straight thread UNC-UNF 60° conforms to ANSI B 1.1

D010-D17/0405



CODE	Nominal size	A	Ø B	Ø C	D	E		
			mm (in)	mm (in)	mm (in)	mm (in)	Nm (lbf in)	Nm (lbf in)
OD	3/4"	1 1/16" - 12 UNF - 2B	42 (1.6535)	24,8 (0.9764)	20 (0.7874)	0,5 (0.0197)	40 ^{+2,5} (354 ÷ 376)	120 ⁺¹⁰ (1062 ÷ 1151)
OF	1"	1 5/16" - 12 UNF - 2B	50 (1.9685) 45 (◆) (1.7717)	30,5 (1.2008)	20 (0.7874)	0,5 (0.0197)	60 ⁺⁵ (531 ÷ 575)	170 ⁺¹⁰ (1505 ÷ 1593)
OG	1" 1/4	1 5/8" - 12 UNF - 2B	60 (2.3622) 58 (◆) (2.2835)	39,1 (1.5394)	20 (0.7874)	0,5 (0.0197)	70 ⁺⁵ (620 ÷ 664)	— 200 ⁺¹⁰ (1770 ÷ 1859)
OH	1" 1/2	1 7/8" - 12 UNF - 2B	65 (2.5591)	45,2 (1.7795)	20 (0.7874)	0,5 (0.0197)	100 ⁺⁵ (885 ÷ 929)	—

(◆) = For MAGNUM 35


01/07.2005

CHANGING ROTATION


Example of changing rotation: from HDP30 pump counterclockwise to clockwise

To change rotation of unidirectional pumps and motors is necessary to operate in the following way:


1. Clean the pump externally with care.
2. Loosen, and remove, the clamp bolts (1).
3. Coat the sharp edges of the drive shaft (4) with adhesive tape and smear a layer of clean grease on the shaft end extension to avoid damaging the lip of the shaft seal when removing the mounting flange.
4. Remove the mounting flange (2), taking care to keep the flange as straight as possible during removal. If the flange is stuck, tap around the edge with a fibre or rubber mallet in order to break away from the body. Ensure that while removing the front mounting flange, the drive shaft and other components remain position.
5. Ease the drive gear (4) up to facilitate removal the front plate (3), taking care that the precision ground surfaces do not become damaged, and remove the drive gear.
6. Remove the driven gear (5) without overturning. The rear plate has not to be removed.



7. Re-locate the driven gear (5) in the position previously occupied by the drive gear (4).
8. Re-locate the drive gear (4) in the position previously occupied by the driven gear (5).
9. Replace the front plate (3) in its original position.



10. Remove the grub screw (6) from the mounting flange (2) and re-locate it in the other threaded hole in the same flange.
11. Gently wipe the machined surface of the mounting flange (2) and the body with a flat hand stone.
12. Refit the front mounting flange (2) turned 180° from its original position.
13. Refit the clamp bolts (1) with the washers and tighten in a crisscross pattern to a torque value of $2230 \div 2726$ lbf in (280^{+28} Nm).



14. Check that the pump rotates freely when the drive shaft (4) is turned by hand. If not a pressure plate seal may be pinched.
15. The pump is ready for installation with the original rotation reversed.

01/07.2005

INSTRUCTIONS

INSTALLATION

Pump

The direction of rotation of single-rotation pumps must be the same as that of the drive shaft. Check that the coupling flange correctly aligns the transmission shaft and the pump shaft. Flexible couplings should be used (never rigid fittings) which will not generate an axial or radial load on the pump shaft.

Motor

The direction of rotation of single-rotation motors must match circuit connections. Check that the coupling flange correctly aligns the transmission shaft and the motor shaft. Flexible couplings should be used (never rigid fittings) which will not generate an axial or radial load on the motor shaft.

TANK

Tank capacity must be sufficient for the system's operating conditions (~ 3 times the amount of oil in circulation) to avoid overheating of the fluid. A heat exchanger should be installed if necessary. The intake and return lines in the tank must be spaced apart (by inserting a vertical divider) to prevent the return-line oil from being taken up again immediately.

LINES

The lines must have a major diameter which is at least as large as the diameter of pump or motor ports, and must be perfectly sealed. To reduce loss of power, the lines should be as short as possible, reducing the sources of hydraulic resistance (elbow, throttling, gate valves, etc.) to a minimum. A length of flexible tubing is recommended to reduce the transmission of vibrations. All return lines must end below the minimum oil level, to prevent foaming. Before connecting the lines, remove any plugs and make sure that the lines are perfectly clean.

FILTERS

We recommend filtering the entire system flow. Filters on suction and return line must be fitted in according to the contamination class as indicated in the first pages of the catalogue. Casappa recommends to use its own production filters:



HYDRAULIC FLUID

Use hydraulic fluid conforming to viscosity data as specified in the first pages of the catalogue. Avoid using mixtures of different oils which could result in decomposition and reduction of the oil's lubricating power.

STARTING UP

Check that all circuit connections are tight and that the entire system is completely clean. Insert the oil in the tank, using a filter. Bleed the circuit to assist in filling. Set the pressure relief valves to the lowest possible setting. Turn on the system for a few moments at minimum speed, then bleed the circuit again and check the level of oil in the tank. In the difference between pump or motor temperature and fluid temperature exceeds 50°F (10 °C), rapidly switch the system on and off to heat it up gradually. Then gradually increase the pressure and speed of rotation until the pre-set operating levels as specified in the catalogue are attained.


PERIODICAL CHECKS - MAINTENANCE

Keep the outside surface clean especially in the area of the drive shaft seal. In fact, abrasive powder can accelerate wear on the seal and cause leakage. Replace filters regularly to keep the fluid clean. The oil level must be checked and oil replaced periodically depending on the system's operating conditions.


01/07:2005

HOW TO ORDER SINGLE UNITS

Before ordering consult shaft, flange and version table compatibility at pages 48 ÷ 50.



HOW TO ORDER DOUBLE PUMPS HDP... / KP20 O PLP20



01/07.2005

MA 02 T A

Edition: 02/06.2012

Replaces: MA 01 T A



Headquarters:

CASAPPA S.p.A.

Via Balestrieri, 1

43044 Lemignano di Collecchio

Parma (Italy)

Tel. (+39) 0521 30 41 11

Fax (+39) 0521 80 46 00

IP Videoconferencing

E-mail: info@casappa.com

www.casappa.com

