



# CORD RING

## DESCRIPTION

Calibrated Cord Ring by the metre

## DYNAMIC SURFACE MATERIAL

Acrylonitrile Butadiene NBR 70 Sh. A -30°C + 110°C.

Silicone MQ -60°C + 230°C.

Viton FKM -20°C + 200 ° C.

### CORD RING

CORD RING NBR 70 Sh.A	
Thickness	±Tolerance
1.78	0.20
2.00	0.20
2.50	0.25
2.62	0.25
3.00	0.25
3.50	0.35
3.53	0.35
4.00	0.35
4.50	0.40
5.00	0.40
5.33	0.40
5.50	0.40
5.70	0.40
6.00	0.40
6.50	0.55
6.99	0.55
7.00	0.55
7.50	0.55
8.00	0.55
8.50	0.55
9.00	0.55
10.00	0.55
11.00	0.65
12.00	0.65
13.00	0.65
14.00	0.65
15.00	0.65
16.00	0.65
18.00	0.85
20.00	0.85
22.00	0.85
25.00	1.00
30.00	1.00

FKM 80 Sh.A CORD RING	
Thickness	±Tolerance
1.78	0.20
2.00	0.20
2.50	0.20
2.62	0.25
3.00	0.25
3.50	0.30
3.53	0.30
4.00	0.30
4.50	0.30
5.00	0.30
5.33	0.30
5.50	0.30
5.70	0.30
6.00	0.30
6.50	0.40
6.99	0.40
7.00	0.40
7.50	0.40
8.00	0.40
8.50	0.40
9.00	0.40
10.00	0.40
12.00	0.50
13.00	0.50
14.00	0.50
15.00	0.50
16.00	0.50
18.00	1.00
20.00	1.00
22.00	1.00
25.00	1.00
30.00	1.30